

FEATURES

ONDA is a surface-mounted luminaire that can enhance and highlight external architectural details.




- Efficacy up to 47 lm/W
- Die-cast aluminium module
- 8 mm thick tempered glass diffuser
- Corrosion and salt water resistant coating
- CRI80
- IP65
- IK07



SPECIFICATION

Luminous Flux	800 Lumens
Colour Temperature CCT	4000K
Power Consumption	17W
CRI	80
Efficacy	47 lm/W
Dimming	Fixed Output 1-10V DALI
Operating Voltage	220 – 230V
Lifetime	50,000hrs
Finish	Grey RAL9007
Installation	Surface Wall
Dimensions	L 400 mm x W 155 mm x H 165 mm
Ingress Protection	IP65
Impact Resistance	IK07
Weight	3.9 kg
Diffuser Material	8mm Tempered Glass
Module Material	Die-cast Aluminium Corrosion/Salt Water Resistant
Operating Temperature	-25°C ~50°C
Conformity	Thermal Management System No UV or IR Emissions, EN60598-1, UKCA, CLASS II
Warranty	5 Years

DIMENSIONS



PRODUCT ORDER CODE

EXAMPLE: ONDA/17W/4K/FO/G

PREFIX	WATTAGE	CCT	DRIVER	FINISH
ONDA	17W	4K 4000K	FO fixed output 10 1-10V dimming DALI DALI dimming	G grey RAL9007