## FEATURES

LIGHTING SOLUTIONS


The EM-SIGN 3 is a high-quality emergency exit sign range that offers a bright 28m viewing distance. Its even illumination across the legend panel ensures maximum visibility in the event of an emergency.

Available in suspended, surface and recessed-mounted options.


EM-SIGN 3 features a unique method of fitting the legend panel screens onto the double-sided, acrylic blades. The EC or ISO legend panels are available in arrow up, arrow down, arrow left or arrow right. The panels are supplied as 'same type' sets of two. When ordering please confirm your panel requirements.

EM-SIGN 3 is specified in a non-maintained or maintained emergency operation. DALI/Self-Test options include an integral DALI self-test gear or standard DALI operation which is fully interoperable when connected to an existing DALI control system.

# DIMENSIONS



**Surface:** the surface and suspended solutions connect with fixing brackets that retain the standard luminaire body via quick release spring clips. For the suspended installation, 1m wire suspension cables are provided.



**Recessed**: the housing has adjustable spring clip arms to simplify installation into different thickness supporting surfaces.

#### SPECIFICATION

Installation	Recessed   Surface   Suspended	
Viewing Distance	28m	
Input Voltage	230V 50Hz	
Colour Temperature CCT	4500K	
Power (Maintained)	Up to 4.4W	
Power (Non-Maintained)	Up to 3.1W	
Duration	3 hours	
Battery Type	4.8V 0/9Ah NiCd	
IP Rating	IP20	
Material	Extruded Aluminium	
Finish	Surface – Silver Aluminium Recessed – White	
Dimensions	Surface – W 300mm x H 220mm Recessed – W 355mm x H 210mm	
Legend Panels	Arrow Up   Arrow Down   Arrow Left   Arrow Right	
Temperature	0°C ~ 25°C	
Weight	3kg	
Conformity	Class I, UKCA	
Warranty	5 Years	

# ĽK 🗵 IP20







# PRODUCT ORDER CODE

EXAMPLE: EM-SIGN 3/SUR/M/S/AR

PREFIX	INSALLATION	EMERGENCY	LEGEND PANELS
EM-SIGN 3	REC recessed	M maintained emergency	AU arrow up
	<b>SUS</b> suspended	<b>NM</b> non-maintained emergency	AD arrow down
	<b>SUR</b> surface	<b>DEM</b> DALI self-test	AR arrow right
			AL arrow left



# 比<u>회</u> IP20

