

Technical features



DALI

Technical data

14 WATT

pre-finish 3 x CREE "XML"

built-in

High corrosion resistance die-cast copper-free aluminum body

Stainless steel AISI 304

Polyester powder coating

with phosphocromating

DMX interface integrated

1 mt. neoprene power cable

DMX IN cable included

Electronic power supply 220/240V 50/60Hz

COLOR RGBW LED

Stainless steel

Silicone rubber

Tempered

included

IP67

IK10

Wattage

IP Rating

IK Rating

Material

Trim

Coating

Screws

Gasket

Glass

DMX

Light source

Transformer

Power cable

DMX cable



DMX










HYDROFLOOR MEDIUM

Ground-recessed luminaire in round shape for outdoor installation, phospho-chromatised and polyester powder coated die-cast copper-free aluminium body and stainless steel AISI 304 frame, tempered safety glass, moulded silicone gasket. Built-in LED driver, DMX driver integrated; with 3 x CREE "XML" RGBW LED. IP67 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
RGBW			
high-power led	12°	480	34.28
high-power led	25°	468	33.43
high-power led	35°	457	32.65

Finish color options:



Stainless Steel

DMX ACCESSORIES

CONTROLLERS, SPLITTERS, ETC...





Gross weight 2,40 Kg