

Technical features



Technical data Wattage

IP Rating

IK Rating

Material

Screws

Light source

Static weight

resistance

Power cable

Gross weight

Included

Gasket

Glass

Remote driver 24V DC

0,8 WATT

Stainless steel AISI 316 NR. 6 x SMD LED

Stainless steel

Max 1000 Kg

Silicone rubber

included

0,30 Kg

included

Tempered, Frosted

1 mt. neoprene power cable

Polypropilene recessing box

IP67

IK09











HYDROFLOOR PICO SOFT

Round ground-recessed luminaire for outdoor installation, stainless steel body and frame, tempered frosted safety glass diffuser, moulded silicone gasket. With 6 x SMD LED. 24V DC remote driver





light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)	
3000°K warm-white				
SMD led	75°	64	80.00	

Finish color options:



Stainless Steel (on request)

Ø 38 mm	
9 mm	100 mm
Ø 28 mm	
Ø 90 mm	
2 30 11111	

remote driver selection						
brand	manufacturer code	type	watt	IP rate	numbers of fixtures	
Meanwell	LPV-20-24	constant voltage 24V DC	20W	IP67	min 1 - max 4	
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	min 1 - max 6	
Meanwell	LPV-60-24	constant voltage 24V DC	60W	IP67	min 1 - max 12	