






## SURF RECESS MEDIUM

Square wall-recessed luminaire for outdoor installation, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, tempered frosted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Built-in LED driver 220-240V 50-60Hz, with 14 CREE XH-G mid-power LED. IP65 rating.



| light source                | light beam options  | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|---|-------------------|------------------------|
| <b>3000°K warm-white</b>    |   |                   |                        |
| mid power led               |  floor washer 180° | 650               | 81.25                  |
| <b>4000°K neutral-white</b> |   |                   |                        |
| mid power led               |  floor washer 180° | 660               | 82.50                  |

**Finish color options:**

-  Textured Grey RAL 9006
-  Anthracite Grey RAL 7016
-  Matt Black (on request)

**Technical features**



**Technical data**

|              |  |
|--------------|--|
| Wattage      | 8 WATT   |
| IP Rating    | IP65   |
| IK Rating    | IK08   |
| Material     | High corrosion resistance die-cast copper-free aluminum body |
| Coating      | Polyester powder coating with phosphochromating pre-finish   |
| Light source | NR. 14 x CREE XH-G LED                                       |
| Screws       | Stainless steel  |
| Transformer  | Electrical power supply 220/240V 50/60Hz built-in            |
| Gasket       | Silicone rubber  |
| Glass        | Tempered   |
| Cable gland  | M16 rubber grommet   |
| Power cable  | 0.10 mt power cable included                                 |
| Gross weight | 1,50 Kg  |
| Included     | Polypropylene housing for recess                             |

