




BOULEVARD MINI 180

600mm height bollard, round shape, for outdoor surface installation, 180° light emission, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 8 CREE JK3030 mid-power LED. IP65 rating.



Ø 110 mm

Technical features



Technical data

reennear aar	•		
Wattage	6.5 WATT		
IP Rating	IP65		
IK Rating	IK10		
Material	High corrosion resistance extruded copper-free aluminum body		
Coating	Polyester powder coating with phosphocromating pre-finish		
Light source	NR. 8 x CREE JK3030 LED		
Screws	Stainless steel		
Transformer	Electrical power supply 220/240V 50/60Hz built-in		
Gasket	Silicone rubber		
Diffuser	Polycarbonate diffuser		
Gross weight	4,00 Kg		



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid-power led	• 180°	400	61.53
4000°K neutral-white			
mid-power led	• 180°	410	63.08

Finish color options:

Textured Grey RAL 9006 Anthracite Grey RAL 7016 Matt Black (on request)

 \square

sales@impactls.com

