




## **BOULEVARD MINI 360**

600mm height bollard, round shape, for outdoor surface installation, 360° light emission, phospho-chromatised and polyester powder coated extruded copper-free aluminium body, polycarbonate diffuser, moulded silicone gasket and stainless steel screws. Anchorage bolts included. Built-in LED driver 220-240V 50-60Hz, with 16 CREE JK3030 mid-power LED. IP65 rating.



ø 110 mm

## **Technical features**



## Technical data

Wattage	12 WATT			
IP Rating	IP65			
IK Rating	IK10			
Material	High corrosion resistance extruded copper-free aluminum body			
Coating	Polyester powder coating with phosphocromating pre-finish			
Light source	NR. 16 x CREE JK3030 LED			
Screws	Stainless steel			
Transformer	Electrical power supply 220/240V 50/60Hz built-in			
Gasket	Silicone rubber			
Diffuser	Polycarbonate diffuser			
Gross weight	4,00 Kg			



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
mid-power led	• 360°	800	66.66
4000°K neutral-white			
mid-power led	• 360°	820	68.33

## Finish color options:

Textured Grey RAL 9006

-

Anthracite Grey RAL 7016

www.impactlightingsolutions.com

01865 989 830

sales@impactls.com

Matt Black (on request)

