

Technical features












DIVE MEDIUM

Underwater projector, surface mounted, completely made in stainless steel AISI 316L, silicone gasket, 24V DC remote driver needed, with 1 x COB LED. IP 68 rating.





| Wattage | 16 WATT | | |
|---------------|--|--|--|
| IP Rating | IP68 - 1 METERS DEPTH | | |
| IK Rating | IK09 | | |
| Material | Completely made in stainless steel AISI 316 L marine grade | | |
| Light source | NR. 1x16W COB LED | | |
| Screws | Stainless steel | | |
| Remote driver | 24V DC NEEDED | | |
| Gasket | Silicone rubber | | |
| Glass | Tempered | | |
| Cable gland | PG11 Cable gland made copper with nickel-coated | | |
| Power cable | 3 mt. neoprene power cable included | | |
| Gross weight | 1.60 Kg | | |

| light source | light beam options | lumen output (lm) | lumin. efficacy (lm/w) | |
|-------------------|--------------------|----------------------|---------------------------|--|
| 3000°K warm-white | | | | |
| cob led | 30° | 1.183 | 73.94 | |

Finish color options:



Stainless Steel

| remote driver selection | | | | | | | | |
|-------------------------|-------------------|-------------------------|------|---------|---------------------|--|--|--|
| brand | manufacturer code | type | watt | IP rate | numbers of fixtures | | | |
| Meanwell | LPV-20-24 | constant voltage 24V DC | 20W | IP67 | 1 | | | |
| Meanwell | LPV-60-24 | constant voltage 24V DC | 60W | IP67 | min 1 - max 3 | | | |

