




I-LINE 6 – MICRO LINEAR

Our I-LINE range delivers sophisticated low-profile micro-linear luminaires, meticulously crafted to excel in discreet accent lighting applications. With a wealth of custom options, their versatile design seamlessly complements a wide array of interior settings, ensuring a tailored lighting solution for every space.

FEATURES

- 56 mm x 13.5 mm plaster-in profile design
- Standard and custom lengths
- Direct lighting distribution
- 3000K, 4000K, tunable white, dim to warm and RGBW
- High lumen efficacy up to 130 lm/W
- CRI90+
- Low-glare polycarbonate diffuser
- Dedicated custom components
- Extruded aluminium channel
- Silver profile finish
- Compact driver
- DALI dimming and Casambi controls
- Plug-and-play wiring for quick installation
- IP20 as standard, IP67 on Request
- 7 year warranty




KLUS Inspiring Solutions


SPECIFICATION

Colour Temperature CCT	3000K 4000K TW D2W RGBW
Installation	Recessed
Distribution	Direct
Diffuser	Opal Clear
Efficacy	Up to 130 lm/W
CRI	90 95
Controls	Fixed Output DALI Casambi
Finish	Silver non-anodised
Dimensions	W 56 mm x H 13.5 mm
Standard Lengths	1000 mm 2005 mm 3010 mm Custom
Operating Voltage	24V
LED Light Source Power	4.8W - 24W
Material	Aluminium
LED Light Source	Max. W 11 mm
Ingress Protection	IP20 IP67
Bending Possibility	No
Lifetime	50,000hrs
Operating Temperature	-25°C ~45°C
Conformity	No UV or IR Emissions, UKCA
Warranty	7 Years
Notes	*Custom lengths available on request, LED light source and lumen efficiency may vary.


DIMENSIONS



PHOTOMETRY



Opal Diffuser



Clear Diffuser

PRODUCT ORDER CODE

EXAMPLE: I-LINE6-S4OSF2005

PREFIX	INSTALLATION	CCT	DIFFUSER	FINISH	DRIVER	LENGTH
I-LINE6 -	R recessed	3 3000K	O frosted opal	S silver	F fixed output	1000 1000 mm
		4 4000K	C clear		D DALI	2005 2005 mm
		TW tunable white			C casambi	3010 3005 mm
		D2W dim2warm				--- custom length*
		RGBW red/green/blue/white				

COMPONENTS



O
opal diffuser



C
clear



A
anodised finish



EC
closed end cap



TECH-KA
protective insert



ZM-60
connector



ZM-180
connector



ZM-NA-120
connector

