















JAZ 1 – TUBE LUMINAIRE

The JAZ 1 is a decorative linear luminaire showcasing a frosted diffuser that delivers smooth and gentle illumination, perfectly suited for architectural applications. Its inconspicuous 30 mm diameter and slender profile extrusion guarantee a minimalist appearance, while a variety of accessories provide versatility.


FEATURES

- **Ø**30
- Dedicated surface and suspension accessory kits
- Direct or direct/indirect light distribution
- 3000K, 4000K, tunable white, dim to warm and RGBW
- High lumen efficacy up to 130 lm/W
- CRI90
- Low-glare polycarbonate diffuser
- Anodised or painted end caps
- Compact driver
- DALI dimming and Casambi controls
- Plug-and-play wiring for quick installation
- IP20 as standard, IP67 on Request
- 7 year warranty



SPECIFICATION DIMENSIONS

Colour Temperature CCT	3000K 4000K TW D2W RGBW			
Installation	Surface Suspended			
Distribution	Direct			
Diffuser	Opal			
Efficacy	Up to 130 lm/W			
CRI	90			
Controls	Fixed Output DALI Casambi			
Finish – End Cap	White Black Anodised			
Dimensions	Ø30			
Standard Lengths	1000 mm 2005 mm 3010 mm Custom			
Operating Voltage	24V			
LED Light Source Power	4.8W - 24W			
Material	Aluminium/Polycarbonate			
LED Light Source	Max. W 8 mm x 2			
Ingress Protection	IP20			
Lifetime	50,000hrs			
Operating Temperature	-25°C ~45°C			
Conformity	No UV or IR Emissions, UKCA			
Warranty	7 Years			
Notes	*Custom lengths available on request, LED light source and lumen efficiency may vary.			





EXAMPLES





PRODUCT ORDER CODE

	DISTRIBUTION	CCT	DIFFUSER	FINISH-ENDCAP	DRIVER	LENGTH
S	D	3	0	А	F	1000
surface	direct	3000K	frosted opal	anodised aluminium	fixed output	1000 mm
SP		4			D	2005
suspended	4000K		W white RAL 9016	DALI	2005 mm	
	TW tunable white	TW			С	3010
		tunable white		B black RAL 9005	casambi	3005 mm
		D2W dim2warm				custom length*
	RGBW red/green/blue/white					
	surface SP	surface direct	surface direct 3000K SP 4 4000K TW tunable white D2W dim2warm RGBW	surface direct 3000K frosted opal SP suspended TW tunable white D2W dim2warm RGBW	surface direct 3000K frosted opal anodised aluminium SP suspended 4000K TW tunable white B black RAL 9005 D2W dim2warm RGBW	surface direct 3000K frosted opal anodised aluminium D SP suspended TW tunable white D2W dim2warm RGBW frosted opal anodised aluminium D D DALI C casambi

EXAMPLE: JAZ1-SD3OAF1000

COMPONENTS





opal diffuser

closed end cap

