




POLI – MICRO LINEAR

The POLI system is meticulously crafted to illuminate surfaces and corners within suspended ceilings and walls, providing the flexibility of complete control over the lighting direction. It includes an adjustable mounting bracket for added versatility in installation.

FEATURES



- 26.1 mm x 7 mm low-profile design
- Standard and custom lengths
- Direct Illumination for coves with a low height
- 3000K, 4000K, tunable white, dim to warm and RGBW
- High lumen efficacy up to 130 lm/W
- CRI90+
- Low-glare polycarbonate diffuser
- Dedicated custom components
- Dedicated adjustable mounting bracket for angle positioning
- Extruded aluminium channel
- Anodised profile finish
- Compact driver
- DALI dimming and Casambi controls
- Plug-and-play wiring for quick installation
- IP20 as standard
- 7 year warranty




SPECIFICATION

Colour Temperature CCT	3000K 4000K TW D2W RGBW
Installation	Surface
Distribution	Direct
Diffuser	Opal Clear
Efficacy	Up to 130 lm/W
CRI	90 95
Controls	Fixed Output DALI Casambi
Finish	Anodised
Dimensions	W 26.1 mm x H 7 mm
Standard Lengths	1000 mm 2005 mm 3010 mm Custom
Operating Voltage	24V
LED Light Source Power	4.8W - 24W
Material	Aluminium
LED Light Source	Max. W 11.2 mm
Ingress Protection	IP20
Angle Adjustment	90°
Lifetime	50,000hrs
Operating Temperature	-25°C ~45°C
Conformity	No UV or IR Emissions, UKCA
Warranty	7 Years
Notes	*Custom lengths available on request, LED light source and lumen efficiency may vary.


DIMENSIONS



PHOTOMETRY



Opal Diffuser



Clear Diffuser

PRODUCT ORDER CODE

EXAMPLE: POLI-S4OAF2005

PREFIX	INSTALLATION	CCT	DIFFUSER	FINISH	DRIVER	LENGTH
POLI -	S surface	3 3000K	O frosted opal	A anodised aluminium	F fixed output	1000 1000 mm
		4 4000K	C clear		D DALI	2005 2005 mm
		TW tunable white			C casambi	3010 3005 mm
		D2W dim2warm				--- custom length*
		RGBW red/green/blue/white				

COMPONENTS



O
opal diffuser



C
clear



A
anodised finish



EC
closed end cap



PK
surface kit
pc

