



## ZARA – Surface

ZARA is a compact surface-mounted downlight with outstanding performance. Its innovative glare control and deep design prioritise visual comfort.


### FEATURES

- Ø152mm
- Efficacy up to 120 lm/W
- Beam angle options
- Optimal low-glare technology UGR>19
- Surface mounted
- Interchangeable reflectors in white, black and silver
- CRI80
- Compact driver
- DALI dimming options
- IP20 ingress protection
- 5 year warranty

## SPECIFICATION

## DIMENSIONS

Colour Temperature CCT	2700K   3000K   4000K
Power	21W   28W
Luminous Flux	2300-3300 lm
Efficacy	Up to 120 lm/W
CRI	80
Controls	Fixed Output   DALI   1-10V
Diffuser	Opal
UGR	<19
MacAdam Ellipse	3
Distribution	Direct
Beam Angle	30°   60°
Finish - Module	White   Black
Finish - Reflector	White   Black   Matt Silver
Dimensions	Ø152 mm x 200mm
Operating Voltage	36V
Current	500mA   700mA
Material	Aluminium
Installation	Surface
Ingress Protection	IP20
Lifetime	50,000hrs L80
Operating Temperature	-25°C ~35°C
Conformity	Thermal management system No UV or IR Emissions, UKCA
Warranty	5 Years



## COLOUR OPTIONS



PRODUCT ORDER CODE

EXAMPLE: ZARA-S21360BWD

PREFIX	INSTALLATION	POWER	CCT	BEAM ANGLE	FINISH	FINISH - REFLECTOR	DRIVER
ZARA -	S surface	<b>21</b> 21W	<b>27</b> 2700K	<b>30</b> 30°	<b>W</b> white	<b>W</b> white	<b>F</b> fixed output
		<b>28</b> 28W	<b>3</b> 3000K	<b>60</b> 60°	<b>B</b> black	<b>B</b> black	<b>D</b> DALI
			<b>4</b> 4000K			<b>S</b> matt silver	<b>10</b> 1-10V