



## TEK 1 – TRACK LUMINIARE

Perfectly supporting European power input voltage ranges, the TEK LED linear luminaire features a tiltable lighting panel, 4/6 wire track rail compatibility, customizable lighting effects, and multiple power channel selection, making it the ideal track luminaire for commercial and industrial applications.



### FEATURES

- Standard lengths
- Single 30° adjustable tilt optic
- Wide range of colour temperature options
- Lumen efficacy up to 175 lm/W
- Offers narrow, medium, wide, and double asymmetrical optics
- Black or white finish
- CRI80/90
- Compatible with 3/4/6 wire track rails
- DALI dimming options
- Quick and easy track installation
- IP20 ingress protection
- 5 year warranty



## SPECIFICATION

Colour Temperature CCT	2700K   3000K   3500K   4000K   5000K 5700K   6500K
Power	20W   50W   60W
Luminous Flux	3200 - 8000 lm
Efficacy	Up to 175 lm/W
CRI	80   90
Controls	Fixed Output   DALI (1500 mm length only)
Beam Angle	30°   60°   90°   Double Asymmetric
Finish	White   Black
Dimensions	W 60 mm x H 10 mm
Standard Lengths	600 mm   1500 mm
Operating Voltage	220-240V 50/60Hz
LED Current	0.35A max
Material	Steel
Adjustability	Single Tilt 30°
Installation	Track
Ingress Protection	IP20
Lifetime	50,000hrs
Operating Temperature	-25°C ~50°C
Conformity	No UV or IR Emissions, UKCA
Warranty	5 Years

## ADJUSTABLE



SINGLE TILT 30°



FLAT

## DIMENSIONS



## OPTIC/BEAM ANGLES



### NARROW 30°



5,600-8,000 lm  
Installation height:  
6-16m



### MEDIUM 60°



5,600-8,000 lm  
Installation height:  
6-16m



### WIDE 90°



5,600-8,000 lm  
Installation height:  
3-5m



### DOUBLE ASYMMETRICAL



5,600-8,000 lm  
Installation height:  
3-4m



PRODUCT ORDER CODE

EXAMPLE: TEK1-T20360BF600

PREFIX	INSTALLATION	POWER	CCT	BEAM ANGLE	FINISH	DRIVER	DIMENSIONS
TEK1-	T track	<b>20</b> 20W	<b>27</b> 3700K	<b>30</b> 30°	<b>W</b> white	<b>F</b> fixed output	<b>600</b> 600 mm
		<b>50</b> 50W	<b>3</b> 3000K	<b>60</b> 60°	<b>B</b> black	<b>D</b> DALI *only available with the 1500 mm length	<b>1500</b> 1500 mm
		<b>60</b> 60W	<b>35</b> 3500K	<b>90</b> 90°			
			<b>4</b> 4000K	<b>A</b> double asymmetric			
			<b>5</b> 5000K				
		<b>57</b> 5700K					