


SPECIFICATION

Distribution	Direct
Colour Temperature CCT	3000K 4000K
Optic/Diffuser	Opal MPO
Output	1 2 3 4
Finish	Grey white black
Efficacy	Up to 125 lm/W
CRI	80+
MacAdam Ellipse	3
Controls	Fixed output DALI Casambi
Installation	Recessed
Dimensions	W 54 mm x H 103 mm
Standard Lengths	L 573 mm – 2958 mm
Connection Options	Start/end middle (for in-line connections)
Material	Extruded aluminium
Ingress Protection	IP40
Impact Rating	IK05
Operating Voltage	220-240V 50/60Hz
Emergency Options	Standard DALI
Lifetime	100000/L80B10
Operating Temperature	-15°C ~35°C, Glow wire test °C: 850
Conformity	UKCA, CE, RoHS, IEC:I
Weight	2.1kg p/m
Warranty	5 Years



DIMENSIONS/PHOTOMETRY



ORDER CODE

SEB54-D-3-O-1-A-597

PREFIX	DISTRIBUTION	CCT	DIFFUSER/OPTIC	OUTPUT	FINISH	LENGTH (mm)		
SEB54-	D Direct	3 3000K	O Opal	1 Low	A Grey RAL9006S	597		
						737		
		4 4000K	MPO Micro-prismatic	2 Standard	W White RAL9003S	877		
						1017		
						3 Medium	B Black RAL9005S	1157
								1297
								1437
								1717
								1997
								2137
								2277
								2557
2977								

OPTIONS

S	Start/end module for connecting continuous systems
M	Middle module for connecting continuous systems
EM	Emergency version 3 hours
EMS	Emergency version equipped with an autonomous testing system 3 hours
EMD	Emergency version 3 hours with DALI interface
D	DALI dimming functionality
C	Casambi wireless lighting controls



STANDARD LENGTHS – 3000K - OPAL

LENGTH (mm)	DISTRIBUTION	CCT	OUTPUT	POWER	DIFFUSER/OPTIC	LUMENS (lm)
597	Direct	3000K	1	6,8W	Opal	728
597	Direct	3000K	2	9,5W	Opal	1003
597	Direct	3000K	3	13,8W	Opal	1402
597	Direct	3000K	4	19,9W	Opal	2103
737	Direct	3000K	1	8,2W	Opal	910
737	Direct	3000K	2	11,6W	Opal	1254
737	Direct	3000K	3	16,8W	Opal	1752
737	Direct	3000K	4	24,6W	Opal	2628
877	Direct	3000K	1	10,1W	Opal	1092
877	Direct	3000K	2	14W	Opal	1504
877	Direct	3000K	3	20,2W	Opal	2103
877	Direct	3000K	4	29,5W	Opal	3154
1017	Direct	3000K	1	11,6W	Opal	1274
1017	Direct	3000K	2	15,9W	Opal	1755
1017	Direct	3000K	3	23W	Opal	2453
1157	Direct	3000K	1	13,1W	Opal	1456
1157	Direct	3000K	2	18W	Opal	2006
1157	Direct	3000K	3	26,3W	Opal	2804
1157	Direct	3000K	4	38,1W	Opal	4206
1297	Direct	3000K	1	14,5W	Opal	1638
1297	Direct	3000K	2	20,2W	Opal	2256
1297	Direct	3000K	3	29,6W	Opal	3154
1437	Direct	3000K	1	16,6W	Opal	1820
1437	Direct	3000K	2	23W	Opal	2507
1437	Direct	3000K	3	31,7W	Opal	3505
1437	Direct	3000K	4	47,6W	Opal	5257
1717	Direct	3000K	1	19,4W	Opal	2184
1717	Direct	3000K	2	27,3W	Opal	3009
1717	Direct	3000K	3	38,1W	Opal	4206
1717	Direct	3000K	4	57,1W	Opal	6308
1997	Direct	3000K	1	22,4W	Opal	2548
1997	Direct	3000K	2	31,5W	Opal	3510
1997	Direct	3000K	3	44,4W	Opal	4906
2137	Direct	3000K	4	71,4W	Opal	7885
2277	Direct	3000K	1	25,3W	Opal	2913
2277	Direct	3000K	2	35,5W	Opal	4011
2277	Direct	3000K	3	50,8W	Opal	5607
2277	Direct	3000K	4	77W	Opal	8411
2557	Direct	3000K	1	27,5W	Opal	3277
2557	Direct	3000K	2	40W	Opal	4513
2557	Direct	3000K	3	57,1W	Opal	6308
2557	Direct	3000K	4	82,9W	Opal	9462
2977	Direct	3000K	1	32W	Opal	3823
2977	Direct	3000K	2	46,1W	Opal	5265
2977	Direct	3000K	3	66,7W	Opal	7360

STANDARD LENGTHS – 4000K - OPAL

LENGTH (mm)	DISTRIBUTION	CCT	OUTPUT	POWER	DIFFUSER/OPTIC	LUMENS (lm)
597	Direct	4000K	1	6,8W	Opal	760
597	Direct	4000K	2	9,5W	Opal	1046
597	Direct	4000K	3	13,8W	Opal	1462
597	Direct	4000K	4	19,9W	Opal	2193
737	Direct	4000K	1	8,2W	Opal	949
737	Direct	4000K	2	11,6W	Opal	1308
737	Direct	4000K	3	16,8W	Opal	1828
737	Direct	4000K	4	24,6W	Opal	2742
877	Direct	4000K	1	10,1W	Opal	1139
877	Direct	4000K	2	14W	Opal	1569
877	Direct	4000K	3	20,2W	Opal	2193
877	Direct	4000K	4	29,5W	Opal	3290
1017	Direct	4000K	1	11,6W	Opal	1329
1017	Direct	4000K	2	15,9W	Opal	1831
1017	Direct	4000K	3	23W	Opal	2559
1157	Direct	4000K	1	13,1W	Opal	1519
1157	Direct	4000K	2	18W	Opal	2092
1157	Direct	4000K	3	26,3W	Opal	2925
1157	Direct	4000K	4	38,1W	Opal	4387
1297	Direct	4000K	1	14,5W	Opal	1709
1297	Direct	4000K	2	20,2W	Opal	2354
1297	Direct	4000K	3	29,6W	Opal	3290
1437	Direct	4000K	1	16,6W	Opal	1899
1437	Direct	4000K	2	23W	Opal	2615
1437	Direct	4000K	3	31,7W	Opal	3656
1437	Direct	4000K	4	47,6W	Opal	5484
1717	Direct	4000K	1	19,4W	Opal	2279
1717	Direct	4000K	2	27,3W	Opal	3138
1717	Direct	4000K	3	38,1W	Opal	4387
1717	Direct	4000K	4	57,1W	Opal	6580
1997	Direct	4000K	1	22,4W	Opal	2658
1997	Direct	4000K	2	31,5W	Opal	3661
1997	Direct	4000K	3	44,4W	Opal	5118
2137	Direct	4000K	4	71,4W	Opal	8225
2277	Direct	4000K	1	25,3W	Opal	3038
2277	Direct	4000K	2	35,5W	Opal	4184
2277	Direct	4000K	3	50,8W	Opal	5849
2277	Direct	4000K	4	77W	Opal	8774
2557	Direct	4000K	1	27,5W	Opal	3418
2557	Direct	4000K	2	40W	Opal	4708
2557	Direct	4000K	3	57,1W	Opal	6580
2557	Direct	4000K	4	82,9W	Opal	9871
2977	Direct	4000K	1	32W	Opal	3988
2977	Direct	4000K	2	46,1W	Opal	5492
2977	Direct	4000K	3	66,7W	Opal	7677