




SPECIFICATION

Distribution	Direct
Colour Temperature CCT	3000K 4000K
Optic/Diffuser	Prismatic polycarbonate reflector & lens
Output	1 2 3 4
Finish	Grey RAL7043
Efficacy	Up to 156 lm/W
CRI	80+
MacAdam Ellipse	3
Controls	Fixed output DALI
Installation	Suspended (hook and wire)
Dimensions	Ø410 mm x H 289 mm
Material	Aluminium
Ingress Protection	IP20
Impact Rating	IK08
Operating Voltage	220-240V 50/60Hz
Connection	Push-in terminal, 3x2x2.5mm ²
Lifetime	100000/L80B50
Operating Temperature	0°C ~40°C
Conformity	UKCA, CE, RoHS, IEC:I
Weight	2.5 kg
Warranty	5 years
Optional (please ask)	Cables



DIMENSIONS



ORDER CODE

APO-3-1-G

PREFIX	CCT	OUTPUT	FINISH
APO-	3 3000K	1 Low	G Grey RAL7043
	4 4000K	2 Standard	
		3 Medium	
		4 High	
		5 Plus	

OPTIONS

D	DALI dimming functionality
CABLE-1	Suspension cable 3x0.75mm ² , 2.0m, Transparent
CABLE-2	Suspension cable 3x0.75mm ² , 3.0m, Transparent
CABLE-3	Suspension cable 5x0.75mm ² , 2.0m, Transparent
CABLE-4	Suspension cable 5x0.75mm ² , 3.0m, Transparent

STANDARD SIZES – 3000K – 4000K

DIMENSIONS (mm)	CCT	OUTPUT	POWER	DIFFUSER/OPTIC	LUMENS (lm)
Ø410	3000K	1	27W	Prismatic Reflector	3860lm
Ø410	3000K	2	39W	Prismatic Reflector	5515lm
Ø410	3000K	3	55W	Prismatic Reflector	7721lm
Ø410	3000K	4	71W	Prismatic Reflector	9926lm
Ø410	3000K	5	82W	Prismatic Reflector	11581lm
Ø410	4000K	1	27W	Prismatic Reflector	4200lm
Ø410	4000K	2	39W	Prismatic Reflector	6000lm
Ø410	4000K	3	55W	Prismatic Reflector	8400lm
Ø410	4000K	4	71W	Prismatic Reflector	10800lm
Ø410	4000K	5	82W	Prismatic Reflector	12600lm