SPECIFICATION

Distribution	Direct
Colour Temperature CCT	3000K | 4000K
Optic	Faceted reflector 40°
Output	1 | 2 | 3
Finish	White RAL9016
Efficacy	Up to 134 lm/W
CRI	80+
MacAdam Ellipse	3
Controls	Fixed output | DALI | Casambi
Installation	Surface | suspension kit
Dimensions	Ø168 x 172 mm
Material	Aluminium
Ingress Protection	IP20
Impact Rating	IK02
Operating Voltage	220-240V 50/60Hz
Lifetime	60000/L80B10
Operating Temperature	0°C ~35°C
Conformity	UKCA, CE, RoHS, IEC:I
Weight	1kg
Warranty	5 Years

DIMENSIONS/PHOTOMETRY







ORDER CODE

ZEN-3-40-1-W

PREFIX	CCT	BEAM ANGLE	OUTPUT	FINISH
ZEN-	**3** 3000K **4** 4000K	**40°** 40° standard	**1** Low **2** Standard **3** Medium	**W** White RAL9016

OPTIONS

SUS	Suspension Wire Kit 1.5m Adjustable, 1pcs
D	DALI dimming functionality
C	Casambi wireless lighting controls

STANDARD DIAMETERS – 3000K– 4000K

DIMENSIONS (mm)	CCT	OUTPUT	POWER	OPTIC	FINISH	CONTROL	LUMENS (lm)
Ø168x172mm	3000K	1	13.5W	40°	White RAL9016	Fixed Output	1715
Ø168x172mm	3000K	2	19.8W	40°	White RAL9016	Fixed Output	2330
Ø168x172mm	3000K	3	26.8W	40°	White RAL9016	Fixed Output	3137
Ø168x172mm	4000K	1	13.5W	40°	White RAL9016	Fixed Output	1813
Ø168x172mm	4000K	2	19.8W	40°	White RAL9016	Fixed Output	2463
Ø168x172mm	4000K	3	26.8W	40°	White RAL9016	Fixed Output	3316