





SPECIFICATION

Distribution	Direct/indirect
Colour Temperature CCT	3000K 4000K
Optic/Beam	Standard 15° Lens
Output	10.5W 12.5W
Finish	Grey RAL7043
Efficacy	100 lm/W
CRI	80+
SDCM	5
Controls	Fixed output
Installation	Surface-mounted
Connection	On the wall. Screw terminal, 3x1x1.5 mm2
Length	137 mm
Width	55 mm
Height	162 mm
Material	Aluminium/tempered glass
Ingress Protection	IP65
Impact Rating	IK08
Operating Voltage	220-240V 50/60Hz
Lifetime	50000/L80B50
Operating Temperature	-30°C ~45°C
Conformity	UKCA, CE, RoHS, IEC:I
Weight	0.8kg
Warranty	5 Years



DIMENSIONS/PHOTOMETRY



15° Lens



ORDER CODE

INDI-DI-3-G

PREFIX	DISTRIBUTION	CCT	OPTIC/BEAM	FINISH
INDI-	DI Direct/indirect	3 3000K 4 4000K	15 15° lens	G Grey RAL7043

STANDARD – 3000K – 4000K

TYPE	CCT	OPTIC/BEAM	POWER	IP	IK	LUMENS (lm)
INDI	3000K	2°	12,5W	IP66	IK08	770lm
INDI	3000K	8°	10,5W	IP66	IK08	1010lm
INDI	4000K	12°	12,5W	IP66	IK08	800lm
INDI	4000K	30°	10,5W	IP66	IK08	1050lm

