




SPECIFICATION

Distribution	Direct
Colour Temperature CCT	3000K 4000K
Optic	Standard diffused glass
Output	8.5W
Finish	Grey RAL7043
Efficacy	103 lm/W
CRI	80+
SDCM	5
Controls	Fixed output
Installation	Wall-mounted
Connection	On the wall. Screw terminal, 3x1x2.5 mm ²
Length	111 mm
Width	95 mm
Height	111 mm
Material	Aluminium/tempered glass
Ingress Protection	IP65
Impact Rating	IK08
Operating Voltage	220-240V 50/60Hz
Lifetime	50000/L80B50
Operating Temperature	-30°C ~45°C
Conformity	UKCA, CE, RoHS, IEC:I
Weight	0.6kg
Warranty	5 Years



DIMENSIONS/PHOTOMETRY



ORDER CODE

RIG-3-G

PREFIX	CCT	FINISH
RIG-	3 3000K 4 4000K	G Grey RAL7043

STANDARD – 3000K – 4000K

TYPE	CCT	OPTIC/BEAM	POWER	IP	IK	LUMENS (lm)
RIG	3000K	Diffused	8.5W	IP65	IK08	840lm
RIG	4000K	Diffused	8.5W	IP65	IK08	875lm

