



SPECIFICATION

Type	LED street luminaire	
Distribution	Direct	
Beam Angle	LSM1 standard (other options available)	
Optic/Diffuser	Lenses, tempered glass diffuser	
Power	36.2W 51W 67.2W 78.4W	
Colour Temperature CCT	4000K	
Efficacy	161lm	
CRI	70+	
Finish	Black grey RAL7021	
SDCM	5	
Controls	Fixed output DALI	
Installation - Pole Ø60mm	Horizontal	Vertical
Adjustable	Tilt +/- 90 degrees	Tilt +/- 90 degrees
Connection	Cable, 3.0m, 3x0.75mm ²	
Dimensions	L 672 x W 490 x H 91 mm	
Material	Aluminium	
Ingress Protection	IP66	
Impact Rating	IK08	
Operating Voltage	220-240V, 0-50-60Hz	
Lifetime	100000/L90B10	
Operating Temperature	-40°C ~40°C	
Conformity	UKCA, CE, RoHS, IEC:I	
Weight	9kg	
Optional	Wall bracket protection class II	
Warranty	5 Years	



DIMENSIONS/PHOTOMETRY



ORDER CODE

TYN-A-4-LSM1-51W

PREFX	CCT	OPTIC/BEAM	OUTPUT
TYN-A-	4 4000K	LSM1 Asymmetric	36.2W Low 51W Standard 67.2W Medium 78.4W High

OPTIONS

TYN-A-ACC-II	Electric Shock protection class II
TYN-A-ACC-CBF3	Outgoing flexible cable 3x1.5mm ²
TYN-A-ACC-CBF5	Outgoing flexible cable 5x1.5mm ²
TYN-A-ACC-WALL	Wall bracket, pole diameter D60mm, 10° angle, 1pcs



STANDARD – 4000K – LSM1

DIMENSIONS (mm)	CCT	POWER	OPTIC/BEAM	LUMENS (lm)
672x490x91mm	4000K	36,2W	LSM1	5820lm
672x490x91mm	4000K	51W	LSM1	7923lm
672x490x91mm	4000K	67,2W	LSM1	9891lm
672x490x91mm	4000K	78,4W	LSM1	11255lm