




SPECIFICATION

Type	LED street luminaire	
Distribution	Direct	
Beam Angle	LS140 standard (other options available)	
Optic/Diffuser	Lenses, tempered glass diffuser	
Power	36.2W 51W 67.2W 78.4W	
Colour Temperature CCT	4000K	
Efficacy	161lm	
CRI	70+	
Finish	Black grey RAL7021	
SDCM	5	
Controls	Fixed output DALI	
Installation	With bracket on 12mm horizontal line.	
Adjustable	Horizontal Tilt +/- 30 degrees	Vertical Tilt +/- 30 degrees
Connection	Push-in terminal, 3x2x2.5mm ²	
Dimensions	L 490 x W 490 x H 130 mm	
Material	Aluminium	
Ingress Protection	IP66	
Impact Rating	IK08	
Operating Voltage	220-240V, 0-50-60Hz	
Lifetime	100000/L90B10	
Operating Temperature	-40°C ~40°C	
Conformity	UKCA, CE, RoHS, IEC:I	
Weight	8.3kg	
Optional	Two level driver protection class II	
Warranty	5 Years	



DIMENSIONS/PHOTOMETRY



ORDER CODE

TYN-B-4-LS140-51W

PREFX	CCT	OPTIC/BEAM	OUTPUT
TYN-B-	4 4000K	LS140 140° standard	36.2W Low 51W Standard 67.2W Medium 78.4W High

OPTIONS

TYN-B-ACC-ADIM	Driver with autonomous two-level dimming
TYN-B-ACC-II	Electric Shock protection class II
TYN-B-ACC-CBF3	Outgoing flexible cable 3x1.5mm ²
TYN-B-ACC-CBF5	Outgoing flexible cable 5x1.5mm ²



STANDARD – 4000K – LS140

DIMENSIONS (mm)	CCT	POWER	OPTIC/BEAM	LUMENS (lm)
490x490x130mm	4000K	36,2W	LS140	5820lm
490x490x130mm	4000K	51W	LS140	7923lm
490x490x130mm	4000K	67,2W	LS140	9891lm
490x490x130mm	4000K	78,4W	LS140	11255lm