


SPECIFICATION

Features	Dimming halo LED shows charge and fault status – ideal for discreet night-time use.
Input Voltage	4V DC Max.
Power	3W
Forward Current	700mA
Light Source	LED - Samsung
Beam Angle	135° - open area lens
Colour Temperature CCT	6500K
Luminous Flux	268 Delivered Lumen @ 700mA
CRI	>75
Emergency Function	Standard non-maintained   DALI self-test maintained
Installation	Recessed
Wiring Method	Series connection only via C4201 Series Plug
Ingress Protection	IP20
Module Dimensions	Ø 50mm x 45mm (Min Void Depth 55mm)
Cut-out Dimensions	Ø 40mm x 43mm
Finish	White RAL9016
Weight (with LED)	0.044kg
Emergency Halo Function	Green indicates healthy charge, red indicates a self-test fault.
Tc Max	80°C LED Back plate
Conformity	BS 60598-1:2021+A11:2022, BS 61347-1:2015+A1:2021, BS 61547:2009, UKCA
Warranty	5 Years



DIMENSIONS



PRODUCT ORDER CODE

CODE	PRODUCT SPECIFICATION
EM-LP-DL-REC-OA-DIM-NM	Recessed Downlight - Open Area, Stand, Non-maintained, White
EM-LP-DL-REC-OA-DIM-DALI	Recessed Downlight - Open Area, DALI, Self-test, Maintained, White

SPACING TABLE

Mounting Height	To Wall		Between Fittings	
	0.5 Lux	1.0 Lux	0.5 Lux	1.0 Lux
2.5m	5.4m	4.5m	12.6m	10.7m
3.0m	5.9m	4.7m	14m	11.7m
4.0m	6.6m	-	16.2m	13.2m
5.0m	0.3m	-	17.8m	0.7m
6.0m	-	-	19m	-
8.0m	-	-	-	-